

DS-PD2-T10AME-EH

Wired Triple Signal Detector

The DS-PD2-T10AME-EH is a high security outdoor detector, combining established and patented technologies such as Tri-Digital Detection Signal Processing and Tri-Anti-Mask Technology which have been adapted to enhance performance in extreme outdoor conditions.



AVAILABLE MODEL

DS-PD2-T10AME-EH	Wired Triple Signal Detector
DS-PDB-EX-Wall bracket	Wall bracket (Need to order separately)
DS-PDB-EX-Adapter	Extend coverage to 90 degrees (Need to order separately, using together with DS-PDB-EX-Wall bracket)
DS-PDB-EX-Fixed bracket	Add two detectors back to back to create 20m perimeter protection (Need to order separately)

*All bracket need to order separately.

MAIN FEATURES

- Microwave + two PIR sensors
- Weather Proof sealed optics
- Heavy duty ultraviolet filter
- 10m volumetric coverage
- Tri-Anti-Masking Technology
- Digital Temperature Compensation

SPECIFICATION

Wired Triple Signal Detector	
Detection Range	10 m, detection angle: 90°
Detection Speed	0.25 m/s to 2.5 m/s
Animal Immunity	10 kg
Power Supply	9-16 V DC 13.8 V DC typical
Operation Temperature	-25 °C to 60 °C
Dimension(H × W × D)	188 mm × 84 mm × 77 mm
Weight	300 g
Installation Environment	Outdoor
Installation Height	1.8 to 2.4 m