



HF Adapter

Mechanik
 Anschlüsse: BNC-Kupplung > Cinch-Stecker
 Gewicht: 7 g

Elektrik
 Testspannung: 2000 V~ 1 Min.
 Isolationswiderstand: 1000 MΩ/Min. @ 500 V
 Kontaktwiderstand: 15 MΩ max.
 Impedanz: 50 Ω

Material
 Kontakt: Messing; vergoldet
 Gehäuse: Messing; vernickelt
 Dielektrikum: Teflon; weiß

RoHS-konform

HF Adapter

Mechanical
 Connectors: BNC jack > RCA plug
 Weight: 7 g

Electrical
 Test voltage: 2000 V~ 1 Min.
 Insulation resistance: 1000 MΩ/Min. @ 500 V
 Contact resistance: 15 MΩ max.
 Impedance: 50 Ω

Material
 Contact: Brass; gold-plated
 Housing: Brass; nickel-plated
 Dielectric: Teflon; white

RoHS compliant

Änderungen

Datum	Name	gez.:	Datum	Name	Bezeichnung	Blatt
		tf	24.02.2015	tf	NC 1524 RCA M - BNC F	
		tf	24.02.2015	tf		
			Norm:		Zeichnungs-Nr.:	von
			Änderungen vorbehalten / Subject to change		11355	